PRODUCT FORM

Product Classification (Existing / New)	New	SKU
Name	24" OSC Misting Fan Kit - High Pressure - 1 Fan	
	High Pressure Misting Fans	
	Tilgii Fressure Wilsting Falis	
Features		
Discount (\$)		

		TA	BLE OF COMPONENTS		
Category	Name	SKU	Features	Quantity	Image
Low Pressure Misting Fans	Outdoor Fan - 24 Inch - White	MC17110	■Size: 24" ■©olor: White ■BPM: 1110, AMPS: 2.65, CFM:9100 ■3 speed Pull chain ■Stainless Steel hardware with Durable Corrosion resistant finish ■Motor with thermal Overlade protection industrial Grade aluminum blade ■0 Ft Heavy Duty cord with cord wrap ■Quiet operation ■Eor indoor/ Outdoor Use ■Øsha Approved Grill	1	AC COSCILLATING OUTDOOR FAR OU
Patio Misting	Misting Fan Ring - Stainless Steel - 15" Diameter - 6 Nozzles	MC11207	Stainless Steel Ring Features • Made with Industrial Grade 3/8" Rigid Stainless Steel 316 • Compatible with all High and Mid Pressure Mist Pumps • Pre-threaded nozzle slots for 10/24 Thread • Rated for up to 2000PSI • Attaches to any wall mount, floor or pedestal fan • Includes Push lock Inlet Fitting • Nozzles & Fan Sold Separately • Lifetime Warranty	1	
Misting Pumps	Misting Pump - Oil Less - 1500psi - 0.15 GPM	MC14240	Maximum Pump Speed (0.15/ 0.30 gpm.): 1800 RPM Maximum Inlet Pressure: 100 PSI Minimum Inlet Pressure: (Based on setting on Pressure switch) or Flooded if Pressure switch is bypassed Maximum Outlet Pressure: 1500PSI Maximum Flow: 0.15 GPM, 0.30 GPM (Refer to manufacturing label on pump) Eull load Amps. (0.15/ 0.30 gpm.): 1.38 Amps. /2.15 Amps Moltage: 110V/ 220V AC (Refer manufacturing label on the pump) Noise Level: 75 DB. Maximum Fluid Temperature: For Room Temperature / Cold Water applications only	1	
HP Nylon Tubing	HP Nylon Tubing - Per Foot - High Pressure Tubing - 1/2-OD Max 2000 PSI-Black-Per Ft	MC72030	•1/2 Inch OD • 0.062" Tube Wall • Color:Black • Rating : 1500 PSI	25	
Stainless Steel Misting Nozzles	Stainless Steel Anti-drip Misting Nozzles - 0.006" - Lowest flow	MC41108	Brainlers Steel Fixed Pin Orifice Brass Body Nickel Plating Option Brasant On, Instant OFF mist effect B0-70 Degree Cone Pattern Spray Minimum Working Pressure 150PSI for 0.006" Maximum Working Pressure 2000PSI for all nozzles	1	
Tools	1/4 Inch Stainless Steel Clamps	MC55242	*B/4 Inch *Stainles Steel *Bor Stainless Steel Tubing	1	
Tools	Tube Cutter	MC55140	Tube Cutter for Flexible Tubing	1	
Misting Pump Parts and Accessories	Commercial Filter for Mist Pumps - 5"	MC60500	■NSF Certified Anti-Scale filter with high efficiency TAC technology achieved a 99.6% effectiveness rating in prevention of scaling & corrosion up to 1 year. ■Wailable with various flows. No need for control valve or electricity. ■Widely used in mid to high pressure misting as well as commercial Ac Precooling Systems.	1	
1-4 Push Lock	1/4 Coupling Tee - Push Lock	MC52360	1/4 Coupling Tee - Push Lock, Nickel Plated Brass, 1500PSI Rated		